

Example: SPDT-0A-18A-D-S9

M SPDT - 0 A - 18 A - D - S9 - LP

M VERSION

Standard : -54 ~ +85°C
With TTL : -40 ~ +85°C
With Indicator : -40 ~ +85°C

LOW PIM

Low PIM

TYPE

SPDT
TRAN
SPMT
MSPDT
MTRAN
MSPMT

CONTROL OPTIONS

SPDT / TRAN

Not Specified: Pin Terminal
S9: 9 Pins D-Sub Control
S15: 15 Pins D-Sub Control

SPMT

Not Specified: D-Sub Control
PIN: Pin Terminal Control

CONNECTOR

0: SMA
1: N
5: SC (High Power)
7: 7/16 DIN
9: K (2.92mm)
10: MINI DIN
11: 2.4mm
12: V (1.85mm)

OPTIONS

H: High Power
T: Internal Terminations
- SPDT/SPMT, SMA & K connectors only
D: TTL Drivers with diodes
P: Postive + Common
- Latching or Normally Open only
A: Auto Reset
- SPMT, Latching only
S: Self Cutoff
- Latching only
I: Transient Suppression Didoes
E: Decoder
Y: Moisture Seal
N: Narrow Body
- SPDT only
L: High isolation (90dB)
C: Custom
- Customer specified requirement

ACTUATOR TYPE

A: Failsafe without indicator
B: Failsafe with indicator
C: Latching without indicator
D: Latching with indicator
E: Normally open without indicator
F: Normally open with indicator

FREQUENCY RANGE

03: DC - 3GHz
12: DC - 12GHz
18: DC - 18GHz
26: DC - 26.5GHz
40: DC - 40GHz
43: DC - 43GHz
53: DC - 53GHz
67: DC - 67GHz

ACTUATOR VOLTAGE

A: 12VDC
B: 15VDC
C: 28VDC
D: 24VDC